



kramer

KRT-4

Cable Retractor



KRT-4 is a cable retractor designed for installing in a meeting room, classroom or other AV site. KRT-4 extends a variety of common AV connector types and is easy to install and use

FEATURES

Provides Convenient and Easy-to-Use Connecting - Pull the cable to extend up to 1.8m (5.9ft) from the installation site; the cable automatically locks in position to the desired length. When finished, pull the cable again and it retracts into the housing

Improved Design - Gentle retraction feature extends the life of the cable and connector

Simple and Flexible Installation Options - Install in compatible Kramer TBUS models or attach directly to the underside of a table with a few screws

Available in Most Common AV Connector Types - HDMI, VGA, audio (3.5mm), LAN, USB, USB-C, and DisplayPort



kramer

TECHNICAL SPECIFICATIONS

Ports	1 Female Connector (fixed cable end) for one of the following: VGA, HDMI, Audio, LAN, USB-2.0, USB-3.0, USB-C, 3H2 or DisplayPort 1 Male Connector (retractor cable end) for one of the following: VGA, HDMI, Audio, LAN, USB-2.0, USB-3.0, USB-C, 3H2 or DisplayPort
Video	Max. Resolution (KRT-4-H, KRT-4-DP) 4K@60Hz (4:4:4)
KRT 4-3H2 Extender Additional Specifications	Optional External Power Source – 5V, 150mA micro USB port Maximum Range for 4K@60Hz (4:4:4) Resolution – 10m from extender to display Maximum Range for 4K@60Hz (4:2:0) / 4K@30 – 15m from extender to display Maximum Range for 1080p@60Hz – 15m from extender to display Maximum Resolution – 4K@60Hz (4:4:4) Content Protection – Up to HDCP 2.2
KRT-4-U32/FF Additional Specifications	Max. Data Rate: 10Gbps Power Rating: 60W (20V, 3A) Max. Resolution: 4K@60Hz
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing
Regulatory Compliance (Standards Compliance)	Safety CE Environmental RoHs, WEEE
Enclosure	Type: Plastic (ABS PC) Color: Black Fixed Cable Length: 20cm (7.9") Retractable Cable Length: 180cm (71")
Accessories	Included: 4 M3x8 screws, WCP-(KRT) insert kit
Product Dimensions	20.40cm x 19.20cm x 3.63cm (8.03" x 7.56" x 1.43") W, D, H
Product Weight	0.4kg (0.9lbs) approx
Shipping Dimensions	34.20cm x 26.60cm x 7.20cm (13.46" x 10.47" x 2.83") W, D, H
Shipping Weight	0.5kg (1.1lbs) approx



kramer

CONFIGURATIONS

KRT-4-H	High-speed HDMI with Ethernet cable retractor with HDMI connector
KRT-4-DP	DisplayPort cable retractor with DisplayPort connector
KRT-4-VGA	VGA cable retractor with VGA connector
KRT-4-LAN	CAT 6 cable retractor with RJ-45 connector
KRT-4-A	Audio cable retractor with 3.5mm mini jack connector
KRT-4-USB-3	USB 3.0 cable retractor with USB type-A connector
KRT-4-3H2	High-Speed HDMI 4K cable retractor with PT-3H2 signal extender
KRT-4-U32/FF	USB type-C cable retractor for data, video, and charging